

Grand Shine

TILE COAT

Grand Shine Tile Coat is an advanced water-based exterior coating with special formulation for roof tiles, Kerala bricks, and non-porous clay tiles. It promises to not only safeguard these surfaces from the environment, but also enhance their visual appeal.



PRODUCT BENEFITS

LONG LASTING PROTECTION

It provides a long period performance in the most rainfall regions and harsh environmental conditions with latest acrylic technology.

ADHESION

It provides a better adhesion to the tiles and gives a better film for the roofs.

RESISTANCE AGAINST ALGAE AND FUNGI

It provides an excellent resistance against microbial growth of algae and fungi. Also prevents appearance of algae growth.

5-YEAR WARRANTY


With Grand Shine Tile Coat, you can rest easy knowing that your roof and walls are protected for 5 years! This top-notch coating is backed by a 5-year warranty, so you can trust that it will perform for you for years to come.

COVERAGE

On regular masonry surface by brushing



1 COAT
8 - 10 sq.m/ltr**



2 COATS
4 - 5 sq.m/ltr**

OUR PACKS



1 ltr

4 ltr

20 ltr

FINISH



MATT RICH SHEEN RICH SHEEN HIGH GLOSS

SMOOTH

See sheen levels in technical details

PAINT APPLICATION METHOD

APPLICATION	STEP 1 GRAND SHINE TILE COAT BRUSH / ROLLER	STEP 2 GRAND SHINE TILE COAT BRUSH/ROLLER/ SPRAY
	DILUTION % (BY VOLUME)	30%
THINNER	WATER	WATER
APPLICATION VISCOSITY (SEC)	PASTE FORM	PASTE FORM
RECOATING PERIOD (HOURS)	4 - 6 HRS	4 - 6 HRS

Recoat period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

PRE PAINTING STEPS

SURFACE PREPARATION

Clean the floor thoroughly and remove any existing wax or sealant and fill any cracks or holes with crack filling paste. For new plastered concrete surface allow the surface to be cured for at least three to four weeks.

CLEAN THE FLOOR

Clean the floor thoroughly to remove any dirt, dust, or debris.

REPAIR IMPERFECTIONS

Fill any cracks, holes, or dents with filler and sand smooth.

PRIME THE FLOOR

Apply a suitable primer to the floor to improve adhesion and provide a uniform surface.

TAPE EDGES

Tape off baseboards, molding, and any other areas that you don't want to paint.

ALLOW TIME TO DRY

Give the surface adequate time to dry before proceeding with the painting process.



POST PAINTING CARE

AVOID FOOT TRAFFIC

Avoid walking on the floor for at least 24 hours after painting to allow the paint to fully dry.

AVOID MOISTURE

Avoid exposing the floor to moisture for at least 72 hours after painting to prevent the paint from peeling or chipping.

CLEAN REGULARLY

Regular cleaning will help keep the floor looking its best. Use a gentle cleaner and a soft mop.

AVOID ABRASIVE MATERIALS

Avoid using abrasive materials such as steel wool or scouring pads to clean the floor as they can scratch the surface.

APPLY A SEALER

Consider applying a clear floor sealer to protect the paint and enhance the durability of the finish.

SAFETY PRECAUTIONS

- Read and Follow the Instructions: Read the instructions carefully before using Grand Shine Floor Coat.
- Wear Protective Gear: Wear gloves and a respirator mask to protect yourself from fumes and chemicals.
- Ventilate the Area: Ensure the room is well ventilated during the painting process to avoid inhaling fumes.
- Avoid Skin Contact: Avoid skin contact with the paint and wash your hands thoroughly after handling it.
- Keep Out of Reach of Children: Keep Grand Shine Floor Coat and any related tools out of reach of children.
- Store Properly: Store Grand Shine Floor Coat properly in a cool, dry place to maintain its quality.
- Dispose of Properly: Dispose of unused paint and packaging materials in accordance with local regulations.
- In case of contact with eyes wash with water and if irritation persists you can seek medical attention.