METAL REFINISH





Rubilux Autofast Automotive Finish is an alkyd-based paint that dries quickly and is highly durable. It forms a tough, high-gloss film on metal and wood surfaces, making it ideal for use on furniture, garden sets, bicycles, automotive, and farm equipment. It provides excellent hiding power and a long-lasting finish. It can be used both indoors and outdoors and can also be applied as a top coat over epoxy and chlorinated finishes.

PRODUCT BENEFITS


RAPID DRYING PROPERTY

The paint is highly durable and also dries quickly, making it a convenient and long-lasting option for various surfaces.

REMARKABLE GLOW AND SHINE

This paint is designed to create a strong, attractive, high-gloss coating on wood and metal surfaces. It has excellent hiding properties and a long-lasting finish.





See sheen levels in technical details

PRE-PAINTING MEASURES

- Rubilux Autofast Automotive Finish is suitable for application on primed surfaces such as steel, aluminum, zinc-coated steel, concrete, and fiberglass.
- > Prior to application, the primed surface should be free from grease, oil, dirt, and other loose materials.
- > It is recommended to use suitable primers like Rubilux SKPS Grey, Rubilux Zinc Chromate Yellow Primer, Rubilux Epoxy Primer, or Rubilux Chlorinated Rubber Primer.
- > The primer should be allowed to be hard dry and well cured before applying the Rubilux Autofast Automotive Finish.

PROCEDURE OF APPLICATION

Thoroughly mix the contents before and during application.

FOR BRUSHING

- The primer can be applied without thinning, but some thinning may be necessary for consistency.
- Adding up to 5% of either ST 222 or ET 101 thinner is recommended depending on the desired consistency.

FOR SPRAYING:

• To achieve the desired consistency, it is recommended to add 5 to 10% of either ST 222 Thinner or ET 101 Thinner.