

Rubilux

Crack Fill Paste

Rubilux Crack Fill Paste is a versatile crack-filling compound that is reinforced with fiberglass, suitable for use on both interior and exterior surfaces. Its exceptional ability to bridge cracks, especially plaster cracks up to 3 mm in size, sets it apart from other options in the market.

PRODUCT BENEFITS:

ABILITY TO FILL CRACKS

It has a remarkable capability to fill cracks up to 3mm wide.

FLEXIBILITY

This product possesses a high-elongation film that can accommodate movement.

MECHANICAL STRENGTH

It is reinforced with glass fibers thus providing superior mechanical strength.

WATER RESISTANCE

It features a water-resistant film that prevents water from seeping through cracks.

ADHESION

It exhibits strong adhesion on all absorbent surfaces, such as plaster, wood, gypsum, POP, asbestos, and more.

USER-FRIENDLY

This single-pack product is ready-to-use and easy-to-apply.

OVERCOATING

It can be easily overcoated by emulsion paints, making it a versatile and convenient solution.

OUR PACKS



COVERAGE

For plaster cracks of 3mm width 5mm depth recommended system is



2 COATS
75 Running ft/kg

COVERAGE



Can be used for cracks on all interior and exterior absorbent surfaces, cracks and gaps caused by drying and shrinkage.

PAINT APPLICATION METHOD

APPLICATION	STEP 1 CRACK FILL PASTE PUTTY KNIFE / TROWEL	STEP 2 CRACK FILL PASTE PUTTY KNIFE / TROWEL	STEP 3 LEVELING	STEP 3 PRIMER AND TOP COAT
THINNER	N/A	N/A	LEVEL THE WALL USING ASIAN PAINTS WALL PUTTY	CONTINUE NORMAL PAINTING USING PRIMER AND TOPCOAT
DILUTION % (BY VOLUME)	N/A	N/A		
APPLICATION VISCOSITY	N/A	N/A		
RECOATING PERIOD	4 - 6 HRS	4 - 6 HRS		

PRE-PAINTING MEASURES

CLEANING

To ensure good adhesion of Crack Fill Paste to the surface, first, use a cutter to open and widen the cracks to form a 'V-shaped groove. This will provide a strong base. Next, thoroughly clean the area to remove any dust or loose particles.

PRIMING

After cleaning the cracks, apply primer on the opened cracks.



AFTER-PAINTING MAINTENANCE

To ensure optimal paint performance, it is advisable to carry out regular cleaning and washing to remove any algae or fungi growth every six months.

CAUTIONARY MEASURES

- ◆ Avoid applying the product on cracks wider than 3mm or on wet surfaces.
- ◆ Only use the product on plaster cracks and not on structural or joint cracks.

SAFETY MEASURES TO ADOPT

- ◆ Keep the container in a cool, dry place with the lid tightly closed and upright.
- ◆ Keep the product out of reach of children and away from food.
- ◆ Seek immediate medical attention if the product is ingested.
- ◆ Wear eye protection during application and rinse eyes immediately with water if contacted.
- ◆ Wash skin with soap and water if the product comes into contact with skin and seek medical attention if irritation occurs.
- ◆ Avoid inhaling vapors or spray and use a suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- ◆ Do not dispose of leftover paint in drains or water courses.
- ◆ In case of spills, use sand or earth to contain spillage.
- ◆ The product does not contain added Lead, Mercury or Chromium compounds.