

# Rubilux

*Acrylic washable distemper*

Rubilux Acrylic Distemper is a water-based, interior wall paint which is a commercial and economical product for consumers to have aesthetic walls at affordable cost.

## PRODUCT BENEFITS

### THE BEAUTIFUL PATINA

Rubilux Acrylic Distemper provides a matt-finish to walls making the wall brighter and fresh in appearance and has a more vibrant color.

### STAIN-RESISTANT


It can provide mild stain-resistant features. It offers many distinctive colors. sleek and non-reflective finish.

### MULTIPLE COLOR VARIANTS

It ensures that the walls maintain their fresh appearance for an extended period by keeping the colors vibrant.

## COVERAGE

On smooth primed masonry surface



**2 COATS**  
85 - 100 sq.ft/kg

## OUR PACKS



## FINISH



MATT    RICH SHEEN    RICH SHEEN    HIGH GLOSS

✓ MATT

See sheen levels in technical details

## PAINT APPLICATION METHOD

APPLICATION	STEP 1 SANDING	STEP 2 CEMENT PRIMER (ST) / CEMENT PRIMER (WT) BRUSH/ROLLER/ SPRAY	STEP 3 ACRYLIC WALL PUTTY PUTTY KNIFE	STEP 4 SANDING	STEP 5 CEMENT PRIMER (ST) / CEMENT PRIMER (WT) BRUSH/ROLLER/ SPRAY	STEP 6 SANDING	STEP 7 FIRST COAT EMULSION BRUSH/ROLLER/ SPRAY	STEP 8 SECOND COAT EMULSION BRUSH/ROLLER/ SPRAY
DILUTION %	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN	BRUSH / ROLLER 8 - 10 SPRAY 15 - 20 80% - 100%	SMALL AMOUNTS TO IMPROVE FLOWABILITY	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN	BRUSH / ROLLER 8 - 10 SPRAY 15 - 20 80% - 100%	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN	BRUSH 65 - 75	BRUSH 65 - 75
THINNER		MTO* WATER	WATER		MTO* WATER		WATER	WATER
APPLICATION VISCOSITY		BRUSH / ROLLER 30 - 40 SPRAY 20 - 25 BRUSH / ROLLER 30 - 40 SPRAY 20 - 25	N/A		BRUSH / ROLLER 30 - 40 SPRAY 20 - 25 BRUSH / ROLLER 30 - 40 SPRAY 20 - 25		BRUSH 20 - 25	BRUSH 20 - 25
RECOATING PERIOD		6 - 8 HRS 4 - 6 HRS	4 - 6 HRS		6 - 8 HRS 4 - 6 HRS		3 - 4 HRS	3 - 4 HRS

## PRE-PAINTING MEASURES

### PLASTERING

When it comes to newly constructed masonry surfaces, it's crucial to exercise patience and allow them to cure completely before moving forward. To ensure that the new masonry surface has adequate time to cure, it is recommended to wait for 28 days before undertaking any further action.

### TIDYING

Before painting, the surface should be thoroughly cleaned and free of any loose paint, dust, or grease. If there is any growth of fungus, algae, or moss, it should be eliminated using a wire brush and water. For areas with excessive dampness, it's recommended to use Rubilux Grand DampProof to prevent further dampness.

### SEALING FOR CRACKS

To seal cracks that are up to 3 mm wide, it is recommended to use Rubilux Crack Fill Paste.

### PATCHING AND LEVELING

If there are any dents or holes on the surface, it's recommended to use Rubilux Acrylic Wall Putty or a mixture of white cement and fine sand in the ratio of 1:3 to fill them up.



## AFTER-PAINTING MAINTENANCE

To eliminate stains, use a moist cloth to wipe them off. It is essential to wait for at least two weeks after application before cleaning to ensure the surface is thoroughly dried.

## CAUTIONARY STEPS

- ◆ Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- ◆ Do not over-thin or over-extend the brush.
- ◆ Stir well and strain before use.
- ◆ Only use Rubilux Paints machine colorants for tinting.
- ◆ After adding the tinter, shake the tinted paint thoroughly both immediately and before use.

## SAFETY MEASURES TO ADOPT

- ◆ To ensure safety when handling this container, keep it in an upright position in a cool and dry place with the lid tightly closed.
- ◆ Keep it away from children and do not store it near food.
- ◆ Swallowing this product can be harmful, and immediate medical attention is necessary if ingested.
- ◆ When using, wear protective eyewear and in case of contact with eyes, rinse thoroughly and seek medical advice.
- ◆ In case of skin contact, wash immediately with soap and water, and seek medical attention if irritation persists.
- ◆ Avoid breathing in vapors or spray and use a nose pad during sanding to prevent dust inhalation.
- ◆ Do not dispose of leftover paint in water sources, and use sand or earth to contain spills.
- ◆ This product does not contain lead, mercury, or chromium compounds.