

# Rubilux

## Synthetic Enamel



Rubilux Synthetic Enamel provides a glossy finish that can transform the appearance of the painted surface. It creates a durable coating that effectively withstands common household stains, offering a reliable shield for the painted surface.

### PRODUCT BENEFITS

#### LUSTROUS FINISH

It provides a shiny, reflective finish that resembles a mirror. It is suitable for painting doors, windows, grills, and gates, creating a glossy and reflective appearance that enhances the visual appeal of these surfaces.

#### STURDY AND RESILIENT

Rubilux Synthetic Enamel is a highly durable and robust paint due to its oil-based film. This feature makes it one of the toughest paints available, providing a protective shield around surfaces.

#### STAIN RESISTANT


Rubilux paint has excellent washability, allowing easy removal of most household stains by wiping them off.

### COVERAGE

On regular masonry surface by brushing



**1 COAT**  
185 - 225  
sq.ft./ltr\*\*



**2 COATS**  
95 - 110  
sq.ft./ltr\*\*

### OUR PACKS



1 ltr



4 ltr



20 ltr

### FINISH

MATT    LOW SHEEN    RICH SHEEN    HIGH GLOSS



## SILKY SMOOTH

See sheen levels in technical details

### PAINT APPLICATION METHOD

APPLICATION	STEP 1 SANDING	STEP 2 RUBILUX ZINC CHROMATE YELLOW PRIMER BRUSH/ROLLER/ SPRAY	STEP 3 RUBILUX ACRYLIC WALL PUTTY PUTTY KNIFE	STEP 4 SANDING	STEP 5 RUBILUX ZINC CHROMATE YELLOW PRIMER BRUSH/ROLLER/ SPRAY	STEP 6 SANDING	STEP 7 RUBILUX SYNTHETIC ENAMEL BRUSH/ROLLER/ SPRAY	STEP 8 RUBILUX SYNTHETIC ENAMEL BRUSH/ROLLER/ SPRAY
THINNER	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN	🔥 MTO*	WATER OR MTO	SAND THE SURFACE WITH SAND PAPER 180 AND WIPE CLEAN	🔥 MTO*	SAND THE SURFACE WITH SAND PAPER 320 AND WIPE CLEAN	🔥 MTO*	🔥 MTO*
DILUTION %		BRUSH 4 - 10 SPRAY 12 - 15	BASED ON REQUIREMENT		BRUSH 4 - 10 SPRAY 12 - 15		BRUSH 8 - 10 SPRAY 15 - 20	BRUSH 8 - 10 SPRAY 15 - 20
APPLICATION VISCOSITY		BRUSH 30 - 40 SPRAY 20 - 25	BASED ON REQUIREMENT		BRUSH 30 - 40 SPRAY 20 - 25		BRUSH 55 - 60 SPRAY 22 - 25	BRUSH 55 - 60 SPRAY 22 - 25
RECOATING PERIOD		6 - 8 HRS	6 - 8 HRS 4 - 6 HRS		6 - 8 HRS		6 - 8 HRS	6 - 8 HRS

## PRE-PAINTING MEASURES

### PLASTERING

When it comes to newly constructed masonry surfaces, it's crucial to exercise patience and allow them to cure completely before moving forward. To ensure that the new masonry surface has adequate time to cure, it is recommended to wait for 28 days before undertaking any further action. This will help to ensure that the masonry surface is stable and ready for subsequent treatment.

### TIDYING

Before painting, the surface should be thoroughly cleaned and free of any loose paint, dust, or grease. If there is any growth of fungus, algae, or moss, it should be eliminated using a wire brush and water. For areas with excessive dampness, it's recommended to use Rubilux Grand DampProof to prevent further dampness.

### SEALING FOR CRACKS

To seal cracks that are up to 3 mm wide, it is recommended to use Rubilux Crack Fill Paste.

### PATCHING AND LEVELING

If there are any dents or holes on the surface, it's recommended to use Rubilux Acrylic Wall Putty or a mixture of white cement and fine sand in the ratio of 1:3 to fill them up.

Do not use Rubilux Synthetic Enamel on surfaces or substrates that are constantly exposed to seepage or moisture.



## AFTER-PAINTING MAINTENANCE

To ensure optimal paint performance, it's recommended that any algae or fungus growth on the painted surface be thoroughly washed and cleaned every six months.

## CAUTIONARY STEPS

- ◆ Avoid applying the paint if the ambient temperature is expected to drop below 10°C within 4 hours of application.
- ◆ Do not dilute the paint excessively or spread it too thinly with a brush.
- ◆ Use only Rubilux machine colorants for tinting.
- ◆ Before use, mix the paint well and remove any impurities.
- ◆ Tinted paints should be shaken thoroughly both after adding the colorant and before use.

## SAFETY MEASURES TO ADOPT

- ◆ Store the container with the lid tightly closed in a cool and dry place, away from children and food.
- ◆ If swallowed, the paint may be harmful, seek immediate medical attention.
- ◆ Wear eye protection while applying the paint, and rinse eyes with plenty of water if there is any contact.
- ◆ Wash skin with soap and water immediately if the paint comes in contact with skin. Seek medical attention if there is irritation.
- ◆ Avoid breathing in vapors or spray. Wear a nose pad while sanding or preparing surfaces to avoid dust inhalation.
- ◆ Do not pour leftover paint down the drain or in waterways. Use sand or earth to contain spills.
- ◆ The paint does not contain lead, mercury or chromium compounds.